



Festif Linear 1200

Festif Linear 1200

REQUIREMENTS

- Low Voltage (24VDC) – Do not wire directly to mains power
- Must be installed with the supplied remote driver
- Must be installed with junction boxes or strong support (junction box is not included)
- Cut-out hole 100-115 mm (varies with junction box size)
- Installation must be carried out by a licensed electrician

APPLICATIONS

- Indoor use only
- Suitable for living room, dining table, bar, kitchen island, entryway, hotels, and restaurants

TYPE OF LIGHTING

Ambient and task lighting (depending on installation height and LED colour)

TECHNICAL DATA

- IP Rating: IP20
- CRI: 98
- Lumen Output: 1800 lm per metre
- Dimmable: Yes (DALI, Triac)
- LED Replaceable: Yes
- Voltage: 24 VDC
- Wattage: 15 W per metre
- LED Colour Options: 2700 K, 3000 K, 4000 K
- Drivers: 100 W (per 5 metre) – Included
- Driver Dimensions: approx 190 × 50 × 30 mm
- LED Lifespan: 50,000 hours
- Certifications: AS/NZS 60598.2, 3820, 61347, 4879, 3000; EN IEC 60598-2-1; UL 1598 / CSA C22.2 No. 250.0 / ANCE NMX J 307/1

MATERIALS

Solid brass, braided fabric cover over flexible LEDs

METAL FINISHES

Natural Brass, Brass H59, Satin Chrome, Brushed Copper, Satin Nickel, Satin Bronze Dark


WARRANTY

- 4 years (residential)
- 2 years (commercial)

DESIGN & MANUFACTURE

Designed and made in Sydney, Australia by D.Bianco

Festif Linear 1200



NOTE: The overall length and drop are approximate and may vary with the design arrangement of the braided LED rope.